



1,2 VK

Volume (+/- 1%)

Volume under lid::	1,24 L
Volume brim full	1,34 L

Dimensions (+/- 1%)

Shape:	Square
Top dimensions:	130 x 130 mm
Bottom dimensions:	102 x 102 mm
Height without lid:	117 mm
Height with standard lid:	118 mm



Weight (+/- 3%)

Bucket without handle:	40 gr.	-	= steel handle	No	- gr
Standard lid:	10 gr	GR	= steel handle + roller grip	No	- gr
		KBKT	= plastics handle on collar	Yes	1 gr

Performance

Stackability - dynamic:	Max: Not available	* Maximum topload on bottom container
-------------------------	--------------------	---------------------------------------

Stacking tests: The stacking tests have been performed with the standard raw material as stated above at 23°C cover a period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, costumers should make internal trials to determine the viability of stacking and transportation.

Lidding options

Standard:	1,2 VK	Tamper evident:	Yes
Seal lid:	1,2 VK SEAL	Alternative lid available:	Not available

Decoration

In mould labeling:	Yes	Dry-offset printing:	No
--------------------	-----	----------------------	----

Packing

On standard pallet (1200x1000)	2808	On europallet (1200x800)	Not available
--------------------------------	------	--------------------------	---------------

Raw Material

Material:	PP Copolymer, Food approved.	Hot filling:	85-95°C
-----------	------------------------------	--------------	---------

Hot temperatures:

The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging becomes flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. This packaging must be tested by costumer with the actual product before approval for use at hot temperatures.

Cold temperatures:

Freezing conditions require special resins available on request. This packaging must be tested by the costumer with the actual product before use at low temperatures.

Quality Specifications:

Compliance: All Dijkstra Plastics products comply with the European Union Commission Regulation No. 10/2011/EC with ammendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the costumer to ensure that the supplied product is suitable for the intended use.

Shelf life: The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low or very high temperatures over a longer period.

Quality information: Deviations in the product specifications in this data sheet of 0,025% or less (i.e. 25 items per 100,000 pcs) are considered acceptable in the industry and therefore cannot be constructed as a defect. Also, please refer to the General Sales and Delivery conditions in force at the time of delivery.

